



TLU

产品概述

TLU

4~20mA

RS-485

GB/T 778-2018

JJG 162-2019

主要优势

-
- 8
-
- TLU-A R400 TLU-C R500
- IP68
-
-
- 72
- 4-20mA RS485 GPRS/NB-IoT

技术参数

性能	参数内容	
型号	TLU-A型	
管径范围 (mm)	D	DN40-DN300
		00
		1级、2级
		DN40-DN50 DN80-DN300

Q_3/Q_1	$Q_1(\text{m}^3/\text{h})$	$Q_2(\text{m}^3/\text{h})$	$Q_3(\text{m}^3/\text{h})$	$Q_4(\text{m}^3/\text{h})$	
	0.1575	0.252	63	78.75	
160	0.40	0.64	160	200	
200	0.625	1.00	250	312.5	
250	1.575	2.52	630	787.5	2
400	2.5	4.00	1000	1250	
	4.0	6.40	1600	2000	
	6.25	10.00	2500	3125	

Q_3/Q_1	$Q_1(\text{m}^3/\text{h})$	$Q_2(\text{m}^3/\text{h})$	$Q_3(\text{m}^3/\text{h})$	$Q_4(\text{m}^3/\text{h})$	
	0.10	0.16	25	31.25	
160	0.08	0.128	40	50	
200	0.2	0.32	100	125	1
250	0.32	0.512	160	200	
500	0.8	1.28	400	500	2
	1.26	2.016	630	787.5	
	2.00	3.2	1000	1250	
	2.00 3.2	3.2 5.12	1000 1600	1250 2000	